

# Power Application Equipment

For carton sealing


**SIGNODE®**

## CaseLocker™ Heavy-Duty Tape Heads

Little David CaseLocker tape cartridges offer sealing solutions for a wide variety of applications.

Each tape head can be outfitted with low tape/no tape sensors to minimize downtime, or air cylinders to retract the

wipe down arms to bypass totes or pre-sealed cartons that do not require tape sealing.



### LD-Xss

Semiautomatic Uniform Washdown Case Sealer. Available with 2" or 3" heads



### Legend

Semiautomatic Random Case Sealer. Available with 2" or 3" heads



### LD-7

Automatic Uniform Case Sealer. Available with 2" or 3" heads



Package Size	Length	Width	Height	Length	Width	Height	Length	Width	Height	
Minimum	4-1/2"	4"	4-1/2"	6"	4-1/2"	2-5/8"	Minimum	4-1/2"	4-1/2"	4-1/2"
Maximum	N/A	28"	24"	N/A	22"	24"	Maximum	N/A	22"	24"
Maximum Weight	Up to 40 lbs.			Up to 40 lbs.			Maximum Weight	Up to 50 lbs.		
Tape Roll Diameter	16"			16"			Tape Roll Diameter	16"		

### Features

- Heavy duty stainless steel design
- Maintenance-free operation
- Lubrication-free tape heads
- Anti-microbial easy clean design
- UL approved
- Available in top and bottom belt design
- Interchangeable tape heads
- Quick, easy changeovers on tape rolls
- Rugged construction
- Maintenance-free operation
- Lubrication-free tape heads
- UL approved
- Interchangeable tape heads
- Quick, easy changeovers on tape rolls
- Can process cartons as low as 2" tall
- Rugged construction
- Maintenance-free operation
- Lubrication-free tape heads
- UL approved
- Interchangeable tape heads
- Quick, easy changeovers on tape rolls
- Available in top and bottom belt design

### Specifications

**Drive speed:** 80' per minute

**Controls:** Allen-Bradley

**Electrical:** 110 volts, 1 phase, 60 Hz

**Machine operating height:**  
Adjustable from 24" to 30"

**Machine dimensions:**  
39-7/8" L x 34-3/8" W x 58-1/4" H.

**Shipping weight:** 269 lbs. (uncrated)

**Drive speed:** 80' per minute

**Controls:** Allen-Bradley PLC

**Electrical:** 115-220 volts, 1 phase, 60 Hz

**Air requirements:** 85 psi @ 10 cfm.

**Machine operating height:**  
Adjustable from 24" to 30"

**Machine dimensions:**  
37-5/16" L x 30-3/16" W x 61-3/16" H.

**Shipping weight:** 230 lbs. (uncrated)

**Drive speed:** 80' per minute

**Controls:** Allen-Bradley PLC

**Electrical:** Two gear motors; 1/6 hp, 110 volts, 1 phase, 60 Hz

**Air requirements:** 70 psi @ 4 cfm.

**Machine operating height:**  
Adjustable from 24" to 30"

**Machine dimensions:**  
36-1/4" L x 31-1/4" W x 57-1/2" H.

**Shipping weight:** 196.5 lbs. (uncrated)