













pack

bundle

nitize warehouse transport



Lowers Wrapping Cost

Innovative high-strength composition enables less film per load

Reduces Waste

Unique manufacturing technique reduces product waste

Improves Load Performance

Contracts around load post-wrapping increasing stability throughout the transportation cycle

Simplifies Use

Lightweight design and easy application



GaleWrap Oriented stretch film

GaleWrap oriented stretch film, unlike conventional hand film, provides optimal load protection, while increasing wrapping productivity. GaleWrap can be used either by hand or in conjunction with GaleWrap Automation Concepts.

Features and benefits

Improves load containment

GaleWrap is manufactured with a proprietary process resulting in film contraction post-application. This coupled with superior puncture resistance provides improved load containment, enabling reliable performance throughout the transportation cycle.

Minimizes consumable costs and product waste

As an oriented film, GaleWrap doesn't neck down during wrapping, allowing operators to use fewer revolutions to provide maximum product protection, while reducing overall expenses. Plus, GaleWrap features hemmed edges, enabling use of the entire roll, reducing product waste.

Reduces heavy lifting

Lightweight rolls simplify applications. GaleWrap corners are secured by simply tugging at the edges, which help provide secure load containment.





437-085

37









pack

bundle

unitize

warehouse transport

| Oriented Stretch Film Technical Specifications | | | | |
|--|---------------|----------------|-----------|------------------|
| Product | Width (in) | Length (ft) | Packaging | Rolls/ Pallet |
| Impact Film | | | | |
| 415-020-IMP | 15 | 2,000 | Bulk | 192 |
| 418-020-IMP | 18 | 2,000 | Bulk | 128 |
| Recoil Film | | | | |
| 415-020-REC | 15 | 2,000 | Bulk | 192 |
| 418-020-REC | 18 | 2,000 | Bulk | 128 |
| Leverage Film | | | | |
| 415-415-LEV | 15 | 1,500 | Case | 144 |
| 418-415-LEV | 18 | 1,500 | Case | 96 |
| Machine Film | | | | |
| 418-085 | 18 | 8,500 | Bulk | 40 |

8,500

Bulk

20

