





bundle





unitize warehouse transpo



## Increases Productivity

"T"-rail pack station and flap folding assist can increase output as much as 40% over hand sealing

# Minimal Setup

Simple no-tools adjustment to change case sizes

# Portbable Design

Ideal for batch runs, economical alternative to a fully-automatic machine

# Simplifies Maintenance

Self-centering belts and lubrication-free tape cartridges for easy operation.



# **SP-304 BO**Semi-automatic, uniform case former

The Little David® SP-304 BO (Bottom Only) is a semi-automatic random case erecting solution capable of facilitating the forming of up to 12 cases per minute\*. The SP-304 BO is an ideal machine for erecting and bottom-sealing random cases for those utilizing a variety of box sizes.

#### Features and benefits

#### Performance

- Plug-in operation
- Universal folding bar folds bottom flaps
- Minimal operator training required
- Self-centering belts
- Custom made "T"-rail pack station made to support your smallest width case size

#### Versatility

■ Tapes boxes from 4-1/2" (114 mm) minimum width

#### Durability

- Sealed drive system
- CaseLocker ST™ tape cartridges requires no lubrication

#### Safety

- Alleviates twisting motion known to cause carpal tunnel syndrome
- Knife guard system of the CaseLocker ST™ tape cartridge allows the blade to be exposed only when the rollers have been depressed

### **Optional equipment**

- Exit roller transfer table
- Casters
- Recommended spare parts kit
- Spare Caselocker tape cartridges
- Additional sized "T" rail (slide on)
- Additional length "T" rail
- Permanently change conveyor height
- 3 phase motor (ecco-saver, higher efficiency)
- NEMA 12 electrical package





SP-304 BO Technical Specifications	
Power	110 volts, 60 cycle, single phase
Operating Speed	72' per minute (18.3 m/min)*
Case Range	Length: 6" - 24" Width: 4-1/2" - 20" Height: 4-1/2" - 24" **
Machine Dimensions	30" high 79 1/2" long 43" wide
Conveyor Height	24 1/4" to 29 1/4" Standard Consult factory for other heights
3-2-1 Limited Warranty	3 Year - Tape Cartridges 2 Year - Complete drive system, motor/ gear reducer 1 Year - All other parts except for wear and moving parts
Closure Material	2" or 3" Pressure Sensitive Tape

- \* Production rate depends on box size & operator dexterity
- \*\* Certain length x width x height combinations may not process due to unstable conveying conditions

