



LITLED DAVID®

PRODUCTS					
SERVICES					
INTEGRATION					
AUTOMATION					
	pack	bundle	unitize	warehouse	transport



Model displayed with optional extras

SP304-E

Semi-automatic uniform case sealer

Operator friendly

Easy to setup and operate. Simple operator controls and all mechanical adjustments.

Engineering quality

Precision Engineering can be defined as painstaking attention to detail. The very essence of Signode.

Simplicity in action

Simple robust construction simple set up, less than 10s changeover from one box size to another. Simple to use. Simple to maintain.

Superb performance

Machine applied tape offers consistency, superior adhesion and a 25% productivity gain over hand-applied tape.



SP304-E

Semi-automatic uniform case sealer



A number of reasons why the unique SP304-E covers your case sealing needs.

Product overview

The Little David SP304-E Pack Station is the complete 'end of line' solution. The SP304-E is a beautifully engineered Semi- Automatic Case Sealer with packing anvil.

Case sealer - flexibility and ease

Amazingly fast changeover between box sizes. Gain a massive 40%-45% packing efficiency as the SP304-E removes 6 flap folding operations away from the packer as well as the taping operation. Single mast technology gives the operator easy access to the front of the machine.

Approved & compliant

- CE certified and independently reviewed for PUWER compliance.
- Quality engineering. Lockable isolator. Separate start/stop correctly colour coded to 60204.

Easy to clean

- All steel construction in standard powder coat.

Improved efficiency

- 40% - 45% efficiency improvement over a manual taping operation, by taking 6 flap folding operations away from the packer as well as the taping. 1 person can do 2 peoples jobs.
- Interchangeable, top and bottom, robust taping cartridge.
- Shelf ready packaging option.

No maintenance

- Simple mechanical flap folding and no pneumatics.

Consistency

- Easy box centralisation due to inter linked side drives.
- Stable empty boxes prior to packing, supported by in feed guides and packing table.

Operator Friendly

- Easy belt replacement as motors below bodyline.
- Transport the machine to where its most effective, with optional caster wheels.

Options

- Outfeed conveyers
- Caster wheels
- Shelf ready
- Paper tape
- 3 phase electrical power

Major Machine Dimensions

Length	2020 mm
Width	859 mm
Operating Height *	575 mm to 762 mm

* Without optional caster wheels.



SP304-E Case Capacity

Minimum case length	152 mm
Maximum case length	610 mm
Minimum case width	114 mm
Maximum case width	508 mm
Minimum case height	120 mm
Maximum case height	610 mm