Edge Protection











bundle

unitize warehouse transport



Jumbo Corner

Plastic corner protection for lashing applications.

Solid protection

Providing strong protection and prevents product damage during transport.

High performance

High quaity product providing top quality protection performance.

Easy to handle

Easy to handle and apply to the corner of the product, holding the strapping in place.

Reusable

Can be used multiple times making it a cost effective option.



JUMBO CORNER

Plastic corner protection for lashing applications











pack

bundle

unitize warehouse transport

Holding strapping and lashing in place, Jumbo Corner wraps around the corner of large products.

Designed for larger strapping used during transportation of cargo on trucks. The product is often used within the paper application, providing a solid corner protection while maintaining the products position during transit.





Jumbo corner applied to paper reels to protect against lashing abrasion.

| Technical Specifications | |
|---|---------------------|
| Material | Polypropylene |
| Max. Width Lashing (mm) | 70 |
| Width Outside (mm) | 150 |
| Length Inside Long Flap (mm) | 180 |
| Length Inside Short Flap (mm) | 130 |
| K-factor* | 1.9 |
| Pcs per Box | 54 |
| Pcs per Pallet | 1,350 |
| Box Size (mm) | 590 x 390 x 410 |
| Weight per Box (kg) | 13.5 |
| Pallet Size (mm) | 1200 x 1000 x 2300 |
| Pallet Weight (kg) | 360 |
| Tolerance Dimensions (mm) | +/- 0.1 |
| Tolerance Weights | +/- 7% |
| Certified by the Fraunhofer- Institute IML | OE 150 / 2013-07 on |

^{*}The K-factor is defined as the ratio between the material thickness and the neutral fibre axis, i.e. the part of the material that bends without being compressed nor elongated.

