

Cargo Lashing System



C-AS Anchorpoint Lash

One way cargo securing system

Easy to use

Simple to apply, available with multiple accessories to enhance lashing use.

Durable

Can handle a wide temperature resistance from 40°C - 80°C, C-AS Anchorpoint Lashing is weather resistant.

High strength

With a maximum system strength of up to 8000 daN this is a high strength lashing product.

High securing force

Strong and sturdy system. Depending on mass forces during transport; 1, 2, 3 or 4 systems can be used to secure the cargo.

C-AS ANCHORPOINT LASH

One way cargo securing system



Signode C-AS Anchorpoint Lashing is a high strength lashing product designed to withstand up to 6000 and 8000 daN breaking strength.

This product is easy to apply inside the container, attached to anchorpoints, acts like a harness behind the load, keeps cargo in place and prevents movement. Limits possible problems when the container doors are opened as load is held in position. Within compliance of international rules and regulations C-AS Anchorpoint lashing supports you to smoothly pass cargo through ports and distribution centres.

Technical Specifications

Name	Length of Coil (m)	Coils per Box	Coils per Pallet	Buckle Type	Quantity Buckles per Box	System Breaking Strength (daN)	Maximum Securing Load (daN)
C-AS Roll	9.5	50	1200	CA-SIG 3516	125	6000	3000
C-AS Roll	10.5	60	1800	CA-SIG 3030	50	8000	4000

Features and Benefits

■ Fast application

C-AS Anchorpoint Lashing is fast to apply and easy to use so the container can be prepared and lashed simply.

■ Minimise damage

The lashing solution will minimise cargo damage, produce will arrive at the destination as required. Lashing will hold cargo in place and prevent items falling out upon opening of container doors.



C-AS Anchorpoint Lash Accessories

When using the C-AS Anchorpoint lashing there are multiple accessories which enhance the use of this fast lashing solution, including:

- Buckles
- Tensioners
- Hangstraps
- Edgeboard 125x125x10
- Container Magnets

To easily connect the lashing to the interior of the container it is possible to use the container magnet accessory. Additional accessories include Hangstraps, Edgeboard (Angleboard) and buckles. The Hangstraps work with a modular system to hold the tension belt in position, this reusable solution is used to attached the upper lashing points to the top of the container. The Edgeboard offers improved protection to the cargo when it is secured on the corners. Buckles assist with the closure of lashing and support the product to be reused. To prepare the C-AS lashing straps inside the container before loading Container magnets can be used.

