

# 4AM-C



## 4AM-C

### Semi-automatic case sealer

#### Productivity Focus

Performance operating speed of 20 meters per minute

#### Easy Maintenance

Easy access to motors, electrical components and belts for maintenance

#### Production Versatility

Wide range of supported case sizes to meet customer requirements

#### Operator Friendly

Easy to operate with simple controls and intuitive tape roll replacement

# 4AM-C

## Semi-automatic case sealer



### Features and Benefits

- Ideal for batch production
- Twin mast column for greater stability during operation
- Separate top and bottom drive for consistent taping
- Uniform and controlled pressure during taping
- Twin flap squeeze rollers secures flap centering
- Blade guards for operator safety
- Built in toolbox
- Self centering side guides for accurate centering
- Positive top and bottom drive to perform sealing of tall and heavy cartons, in additional to regular cartons
- In-built Emergency Stop and LOTO
- Scale for measuring box height



### Utility Requirements

Power	230 VAC, 1 Phase, 50 Hz
Consumption	0.4 KW
Pneumatic	NA

### Case Dimensions

Length	150mm to Unlimited
Width	160mm to 450mm
Height	100mm to 550mm
Weight	2 to 40 Kg
Carton Ply	3 & 5

### Technical Specifications

Tape Head	Standard (2", 2.5", 3")
Tape Roll Length	65 M / 650 M / 1000 M
Machine Length	1080mm
Machine Width	750mm
Machine Height	1530mm
Bed Height	650 to 800 mm (Adjustable)
Weight	143 Kg
Drive Motor	0.25 HP, 2 No.
Belt Speed	20m / minute

### Options Available

- Idle roller conveyor 0.5 / 1.0 meter length
- Safety guards with interlocks