

6AM



6AM

Heavy duty case sealer for tall and heavy cartons

Productivity Focus

Performance operating
speed of 18 meters
per minute

Easy Maintenance

Easy access to motors,
electrical components and
belts for maintenance

Production Versatility

Wide range of supported
case sizes to meet customer
requirements

Operator Friendly

Easy to operate with simple
controls and intuitive tape
roll replacement

6AM

Heavy duty case sealer



Features and Benefits

- Ideal for batch production
- Twin mast column for greater stability during operation
- Separate top and bottom drive for consistent taping
- 3" drive belts for maximum load carrying capacity
- Uniform and controlled pressure during taping
- Twin flap squeeze rollers provide additional pressure for improved top flap alignment
- Built in toolbox
- Self centering side guides for accurate centering
- Positive top and bottom drive to accommodate sealing of tall and heavy cartons, in addition to regular cartons
- Telescopic legs for height adjustment
- Blade guards for operator safety
- In-built emergency stop and LOTO

Utility Requirements

| | |
|-------------|-------------------------|
| Power | 415 VAC, 3 Phase, 50 Hz |
| Consumption | 0.4 KW |
| Pneumatic | NA |

Case Dimensions

| | |
|-------------|---|
| Length (mm) | 150 to Unlimited |
| Width (mm) | 225 to 750 |
| Height (mm) | 120 with 2", 150 with 2.5", 170 with 3" - max.750 |
| Weight (Kg) | 5 to 60 |
| Carton Ply | 3 & 5 |

Technical Specifications

| | |
|------------------|-------------------------|
| Tape Head | Flexible (2", 2.5", 3") |
| Tape Roll Length | 65 M / 650 M / 1000 M |
| Machine Length | 1040mm |
| Machine Width | 1060mm |
| Machine Height | 1700mm |
| Weight* | 198 Kg |
| Drive Motor | 0.25 HP, 2 No. |
| Belt Speed | 18m / minute |



Available Options

- MS/ Polycarbonate machine guards for operator protection
- Customization for 7 ply boxes