Case Bottom Sealer

PRODUCTS
SERVICES
INTEGRATION
AUTOMATION

pack bundle unitize warehouse transport

4 BS

Compact Design

Fits easily into existing layouts, optimizing factory floor space without requiring major setup changes

Flexible Placement

Can be moved or positioned along the packing line as needed, enabling adaptable and efficient

Continuous Performance

Delivers round-the-clock sealing, improving throughput and reducing downtime

Dual-Side Drive System

For consistent and uniform bottom sealing, beneficial for smaller cartons

SIGNODE

4 BS
Bottom Sealing Machine

PRODUCTS
SERVICES
INTEGRATION
AUTOMATION

pack bundle unitize warehouse transport

The Bottom Sealer is the ideal alternative to manual bottom taping. It increases productivity several times over and can easily be attached to a conveyor for on-line operations. All this results in never-before economy and efficiency.



Features

- Provides high-speed sealing, reducing packing time per carton
- Suitable for batch production, delivering better and consistent output
- Two-side drive system (single motor) provides uniform and secure sealing
- Special blower enables continuous and uninterrupted taping
- Can be easily integrated with conveyors for in-line automated operations
- Telescopic legs allow precise height matching with existing conveyor systems
- Adjustable for various carton widths and sizes, supporting diverse SKUs
- Mobile design allows movement across the factory floor as per need
- Easy to operate, requiring minimal operator skill
- Simple adjustment mechanisms for quick changeovers between carton sizes
- No tools required for adhesive tape placement, reducing effort and time
- Compatible with standard tape sizes (650m / 1000m rolls) for cost efficiency
- Optional top platen support provides better sealing when cartons are empty

Category	Parameter	
Machine Dimensions	Length (mm)	1012
	Width (mm)	800
	Height (mm)	1530
Carton Dimensions	Length (mm)	Minimum 150
	Width (mm)	160 to 500
	Height (mm)	120 to 500
Utility Requirements	Power	230 VAC, 1-Phase, 50 Hz,
	Consumption	400 W

*Accommodates 2" & 2.5" wide tape (650m or 1000m)

The company reserves the right to make technical alterations without prior notification.
© 2026 Signode Industrial Group, LLC / 24050 /REV 260706 **www.Signode.com**
For more information contact info.india@signode.com

SIGNODE