


# 5FRM



## 5FRM

### Automatic random case sealer with four-flap closure

#### Productivity Focus

Performance operating speed of 18 meters per minute

#### Easy Maintenance

Easy access to motors, electrical components and belts for maintenance

#### Production Versatility


Wide range of supported case sizes to meet customer requirements

#### Operator Friendly

Easy to operate with simple controls and intuitive tape roll replacement

# 5FRM

## Automatic random case sealer



### Features and Benefits

- Automatic sealing of random size cartons
- Machine automatically adjusts itself to varying size cartons
- Independently controlled top and side drives for smooth flow of cartons
- Easily integrates into production lines
- Automatic On/Off features enables power saving during idle time
- Twin mast column for greater stability during operation
- Pneumatic top drive and side guides align to the carton width and height automatically
- Uniform and controlled pressure during taping
- Belt speed of 18m/minute
- In -built Emergency Stop and LOTO
- Blade guards for Operator safety
- PLC Controlled logic for smooth operation

### Utility Requirements

Model	5FRM Standard	5FRM Small
Power	415 VAC, 3 Phase, 50 Hz	
Consumption	0.6 KW	0.4 KW
Pneumatic	6 Bar 15.8 Liters per cycle	6 Bar 8.6 Liters per cycle

### Case Dimensions

Model	5FRM Standard	5FAM Small
Length	200mm to 570mm	200mm to 400mm
Width	170mm to 450mm	130mm to 320mm
Height	150mm to 400mm	130mm to 300mm
Weight	5 to 50 Kg	
Carton Ply	3 Ply & 5 Ply	



### Technical Specifications

Model	5FRM Standard	5FRM Small
Tape Head	Flexible (2", 2.5")	
Tape Roll Length	65 M / 650 M / 1000 M	
Machine Length	2040mm	1470mm
Machine Width	1065mm	805mm
Machine Height	1700mm	1600mm
Weight*	295 Kg	255 Kg
Drive Motor	0.25 HP, 3 No.	
Throughput Speed	5-7 cartons / minute	8-9 cartons / minute

### Available Options

- MS/ Polycarbonate machine guards for operator protection
- No/Low tape indicator reduces changeover downtime
- Pneumatic RCC - 1000mm(L) X 745mm(W) X 650mm(H)