MB-P











pack

bundle

unitize

warehouse transport



Intuitive Operation

Plug and play design for easy set up

Simplifies Maintenance

Built with high-efficiency components and few wear parts

Production Versatility

Designed for use in many industries and applications

Operator Friendly

Easy to operate with simple controls and intuitive stretch film replacement



MB-P

Automatic off-line strapping machine

PRODUCTS SERVICES INTEGRATION AUTOMATION pack bundle unitize warehouse transport

Features and Benefits

- MS Arch and Steel dispenser for durability and longevity
- Robust and reliable strapping head
- Faster response time and strapping speed
- User friendly adjustment and operation
- Separate tool kit for easy maintenance
- Heavy duty heater
- Easy loading and unloading of strap
- Caster wheels for easy shop floor movement
- Low maintenance cost
- Tension controller inside the machine
- Smoke exhaust system
- Door with electric interlocks for safer operations
- 3 modes of operation Cycle on / Table top / Foot Pedal switch
- PLC HMI for easy access
- Sleep mode for power saving
- Carton counters

Color

- Batch counter for shift / day
- Non-resettable for Total no. of boxes packed
- Alarms and fault warnings for easy identification of problem area
- Multiple straps with one button for faster operation


| Technical Specifications & Dimensions | | | | | |
|---------------------------------------|-------------------------------------|--|--|--|--|
| Power Supply | 415 Volt, 3 Phase, 50 Hz | | | | |
| Power Consumption | 0.85 KW | | | | |
| Strapping Speed | 1.9 Sec / Cycle, 1920 Cycles / Hour | | | | |
| Strapping | 9mm / 12mm / 15mm | | | | |
| Strap Tension | 0.5 to 70 Kg | | | | |
| Package Size (Min) | 100mm Width x 30mm Height | | | | |
| Package Size (Max) | Refer to Chute Arch Sizes | | | | |
| Package Weight | 5 to 40 Kg | | | | |
| Table Top Height | 810mm to Floor | | | | |

PLC with HMI



Chute / Arch Sizes

| \ | | | | | | | | |
|------|-----|-----|------|------|------|------|------|------|
| \ w | 650 | 850 | 1050 | 1250 | 1450 | 1650 | 1850 | 2050 |
| н \ | | | | | | | | |
| 400 | * | * | * | * | * | * | ☆ | ☆ |
| 600 | * | S | * | * | * | * | ☆ | ☆ |
| 800 | * | * | * | * | * | ☆ | ☆ | ☆ |
| 1000 | * | * | * | * | ☆ | ☆ | ☆ | ☆ |
| 1200 | * | * | * | ☆ | ☆ | ☆ | ☆ | ☆ |
| 1400 | * | * | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ |
| 1600 | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ |
| 1800 | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ |
| 2000 | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ |
| 2200 | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ |
| 2400 | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ | ☆ |



Machine Options

- Ball table top for package over 40Kg in weight
- MS / Polycarbonate machine guards for operator safety



Body -Slate Grey, Arch - Jet Black