

Shippers™ Airbags | Inflators

Airbags

◆Type	Weight	Load Capacity	AAR Verified	Standard Valve	Max. PSI	Mode of Transportation				
						Intermodal	Rail	Sea Container	Truck	Vessel
Zebra Kraft Dunnage Airbags										
Abrasion Resistant (AR)	*Lightweight	Less than 45,000 lbs		SuperFlow	2.0			•	•	
Sewn End (SE)	*Lightweight	Less than 45,000 lbs		SuperFlow	2.0			•	•	
Level 1	*Lightweight	Less than 45,000 lbs	•	SuperFlow	3.0	•		•	•	
Level 2	+Heavyweight	Less than 75,000 lbs	•	TX	5.0	•		•	•	
Level 3	+Heavyweight	75,000 to 160,000 lbs	•	TX	8.0		•			
Level 4	+Heavyweight	160,000 to 215,000 lbs	•	TX	10.0		•			
Polywoven Dunnage Airbags										
Gorilla Level 0	*Lightweight	up to 45,000 lbs		SuperFlow	2.0			•	•	
Gorilla Level 1	*Lightweight	up to 45,000 lbs	•	SuperFlow	3.0	•		•	•	
Gorilla Level 2	*Lightweight	up to 75,000 lbs	•	TX	5.0	•		•	•	
Gorilla Level 3	+Heavyweight	75,001 to 160,000 lbs	•	TX	8.0		•			•
Gorilla Level 4	+Heavyweight	160,000 to 216,000 lbs	•	TX	10.0		•			•
Gorilla Level 5	+Heavyweight	up to 216,000 lbs horizontal roll paper applications	•	TX	10.0		•			•
Hippo Square	*Lightweight	Less than 45,000 lbs	F-2 Loading Method	SuperFlow	2.5	•		•	•	
Other Dunnage Airbags										
Big Foot Vinyl	*Lightweight	Less than 45,000 lbs		Turbo Flow	1.5			•	•	
Flex PE	*Lightweight	Less than 45,000 lbs		SuperFlow	0.5			•	•	

◆Part numbers are available to Signode Sales Representatives through PowerBI

*Lightweight airbags have a standard width of 36" and 48" and a length of 36" through 96" / Custom sizes are available

+Heavyweight airbags have a standard width of 36" and 48" and a length of 36" through 120" / Custom sizes are available



Zebra Kraft Dunnage Airbag



Gorilla Polywoven Dunnage Airbag



Hippo Polywoven Square Dunnage Airbag



Big Foot Vinyl Dunnage Airbags



Flex PE Dunnage Airbags

www.signode.com/en-us/products/protective/dunnage-bags

Airbag Inflators

Inflation System	Options	Part Number	For use on these airbags															
			Zebra Kraft Paper						Gorilla and Hippo Square Polywoven						Big Foot Vinyl & Flex PE			
			AR	SE	1	2	3	4	0	1	2	3	4	5	HS	BF	Flex	
Digital	Sleeve Venturi & TX Tip	DI1300				•	•	•				•	•	•	•			
	FastFill MouseTip	DI1600			•	•	•	•										
	FastFill BBS Tip	DI1700			•	•	•	•										
	TX Low Profile	DI1900				•	•	•				•	•	•	•			
SuperFlow®	SuperFlow Inflator with Low Pressure Insert	SF1000	•	•	•					•	•						•	•
	SuperFlow Inflator with High Pressure Insert	SF2000	•	•	•					•	•						•	•
TurboFlow	Plastic Inflator	TF3000								•	•	•					•	
	Metal Inflator	HI1100								•	•	•	•				•	
	Gauged Inflator	TF2000								•	•	•		•	•		•	
Turbo Xtreme (TX)	Gauged	TX2000			•	•	•	•			•	•	•	•	•			
	Without Gauge	HI1300			•	•					•	•						
MAX™ Inflator (Battery)	SF Kit with two batteries and one charger	MA5100	•	•	•					•	•					•	•	•
Turbo Electric	SuperFlow Inflator	SF4000	•	•	•					•	•					•		•
	TurboFlow Inflator	TF4000															•	
Forklift Inflator	15ft hose and attachment clip	MA1000	•	•	•					•	•					•	•	•



Digital Inflation System



SuperFlow® Inflation System



TurboFlow Inflation System



Turbo Xtreme (TX) Inflation System



MAX™ Inflator



Turbo Electric



Forklift Inflator