

4RM



4RM Random Case Sealer

Productivity Focus

Performance operating
speed of 20 meters
per minute

Easy Maintenance

Easy access to motors,
electrical components and
belts for maintenance

Production Versatility

Wide range of supported
case sizes to meet customer
requirements

Operator Friendly

Easy to operate with simple
controls and intuitive tape
roll replacement

4RM

Random Case Sealer



Features and Benefits

- Automatic sealing of random size cartons
- Machine automatically adjusts to varying size cartons
- Suited for random sealing of tall and heavy cartons
- Independently controlled top and bottom drives for smooth flow of heavy cartons
- Ideal for integrating with different production lines
- Auto On/Off enables power saving during idle time
- Twin mast column for greater stability during operation
- Uniform and controlled pressure during taping



Utility Requirements

Power	230 VAC, 1 Phase, 50 Hz
Consumption	0.4 KW
Pneumatic	6 Bar - 9.5 Liters/Cycle

Case Dimensions

Length (mm)	150 to Unlimited
Width (mm)	170 to 450
Height (mm)	120 with 2", 150 with 2.5" - max. 450
Weight (Kg)	2 to 15
Carton Ply	3 & 5

Technical Specifications

Tape Head	Flexible (2", 2.5") *Optional - Standard Head (2", 2.5", 3")
Tape Roll Length	65 M / 650 M / 1000 M
Machine Length	1080mm
Machine Width	570mm
Machine Height	1385mm
Weight	159 Kg
Drive Motor	0.25 HP, 2 No.
Belt Speed	20 m / minute
Throughput	Up to 16 cartons / minute

Available Options

- No/Low tape indicator reduces changeover downtime
- MS/ Polycarbonate machine guards for operator protection