

BXT Go™



BXT Go

Battery Hand Tool for Plastic Strapping



Budget Friendly and Reliable

Engineered in Switzerland, manufactured with high quality components and precise manufacturing standards. A perfect balance between high performance and cost efficiency

Universal Applications

A true all-rounder, reliable tool with clear controls and an intuitive interface, improving process reliability across teams and reducing downtime. A wise choice for standard applications

Lightweight and Versatile

The tool's optimized weight and balance make it exceptionally easy to carry and use, reducing operator fatigue whilst delivering consistent results

Sustainable Design

Every component can be replaced. Metal and plastic parts are made from recycled and recyclable materials

BXT Go™

Battery Hand Tool for Plastic Strapping



A smart choice designed for universal applications, giving you the essential features and high quality. Optimized for 13 and 16 mm straps. Efficient cycle execution and straightforward operation for maximum efficiency.

Features and benefits

■ A great choice for everyday use

The BXT Go strapping tool is the outcome of decades of expertise. Engineered in Switzerland, the BXT Go strapping tool is a robust and affordable all rounder for the professionals seeking a balance between cost and productivity.

■ Increased productivity

Increased efficiency due to fast-charging BOSCH® batteries that require only 24 minutes to charge to 80% capacity.

■ Sustainable design

High-quality metal and plastic parts, made of recycled or recyclable materials. BXT Go tool components are fully replaceable, allowing expanded product lifetime and streamlined tool management.



BXT Go Technical Specifications

Operation Mode	Auto / semi / manual
Tension Force Range	250–2000 N / 56–450 lbf
Tension Speed	145 mm/s (5.7 in/s)
Weight (Incl. Battery)	3.65 kg (8.05 lb)
Dimension (L X W X H)	340 x 149 x 137 mm (13.4" x 5.9" x 5.4")
Working Temperature	–10 °C to +40 °C (14–104 °F)
Relative Humidity	Up to 90%
Sealing (Joint type)	Friction weld seal
Joint Strength (Depends on strap quality)	Up to 80%
Battery / Charger	Bosch GAL 18V-40
Battery Charger Voltage	100 or 110 or 230 V
Battery Type	Bosch Li-Ion 18V, 2.0 Ah
Charging Time	80% in 24 min
Cycles Per Battery Charge	Low tension, up to 650 Medium tension, up to 420 High tension, up to 280
Strap Type	PET (Polyester) and PP (Polypropylene)
Strap Width	13 mm and 16 mm (1/2", 5/8")
Strap Thickness	0.5–1 mm (.019"–.040")

BXT Go Compared to BXT4

Features	BXT Go	BXT4
Maximum Tension Force	2,000 N (450 lbf)	4,500 N (1000 lbf)
Strap Compatibility	13 and 16 mm (1/2", 5/8")	9 to 19 mm (3/8", 1/2", 5/8", 3/4")
Auto / Semi Auto / Manual Modes	■	■
Strapping Alignment Indication	■	■
Strap Dust Blow Through Vent	■	■
Zero Tension Welding	■	■
DEKRA Certification	■	■
EasyTrigger™ Technology	—	■
Touch Display	—	■
Variable Tension Speed	—	■
Soft Operation Mode	—	■
Real Time Indication of Tension Force	—	■
Battery Protection	—	■
Accessories	—	■

More performance and ergonomics?

Discover next level productivity and ease of use with our premium, top performer **BXT4 with EasyTrigger™** technology

